

V-FLEX™ Harness

Technical Data Sheet



CAPACITY	140 Kg
BRAND	MSA
SUB BRAND / MODEL NAME	V-FLEX
SIZES	Extra Small, Standard, Extra Large
D-RING LOCATIONS	Dorsal (back), chest, hips <i>(depends on version)</i>
BUCKLE CONNECTION	Bayonet
PADDING LOCATIONS	Shoulders, Legs, Waist <i>(depends on version)</i>
THREAD/STITCHING	Polyester
WEB	Polyester, Nano-Technology treated
WEB KEEPER	Nylon, Automatic Resetting
LEG BUCKLES	Anodized Forged Aluminum, Stainless Steel Tabs and Adjuster
CHEST BUCKLE	Anodized Forged Aluminum, Stainless Steel Tabs and Adjuster
D-RING	Anodized Forged Aluminum
PRODUCT WEIGHT	1,80 Kg (version without waist belt) 2,88 Kg (version with waist belt)
PRODUCT STYLES	Racing style
FALL INDICATOR	Dual, at the backside
MAXIMUM LIFESPAN	10 years from date of first use
LANYARD KEEPERS	2 at the front, 2 at the waist
FALL INDICATOR	Dual, at the backside
OPERATING TEMPERATURE	-40°C... +50°C
MAXIMUM LIFESPAN	10 years from date of first use
STANDARDS	EN 361:2002, EN 358:2018 <i>(depends on version)</i>



Harness Size Chart

ft. (m)											
6'-6" (2.0)											
6'-4" (1.9)											
6'-2" (1.9)											
6'-0" (1.8)											
5'-10" (1.8)											
5'-8" (1.7)											
5'-6" (1.7)											
5'-4" (1.6)											
5'-2" (1.6)											
5'-0" (1.5)											
lb. (kg)	110 (50)	130 (59)	150 (68)	170 (77)	190 (86)	210 (95)	230 (105)	250 (114)	270 (123)	290 (132)	310 (140)