




# MSA Cable Temporary Horizontal Lifeline



## Technical Data Sheet

			
PART NUMBER	10219288	10219289	10219290
DESCRIPTION	MSA Cable Temporary Horizontal Lifeline, 60 ft. (18 m), Anchor Straps	MSA Cable Temporary Horizontal Lifeline, 60 ft. (18 m)	MSA Cable Temporary Horizontal Lifeline, 100 ft. (30 m)
ANCHOR STRAPS INCLUDED	Yes	No	No
LIFELINE LENGTH	5-60 ft. (1.5-18.3 m)	5-60 ft. (1.5-18.3 m)	5-100 ft. (1.5-30.5 m)
LIFELINE CONSTRUCTION	6 x 19, 5/16 in. (8 mm), fiber core	6 x 19, 5/16 in. (8 mm), fiber core	6 x 19, 5/16 in. (8 mm), fiber core
LIFELINE MATERIAL	Galvanized Steel Cable	Galvanized Steel Cable	Galvanized Steel Cable
CAPACITY	130-310 lb. (59-141 kg)	130-310 lb. (59-141 kg)	130-310 lb. (59-141 kg)
INSTALL TYPE	Temporary/Portable	Temporary/Portable	Temporary/Portable
TURNBUCKLE	Zinc plated Carbon Steel	Zinc plated Carbon Steel	Zinc plated Carbon Steel
THREADED SHAFTS	Stainless Steel, PTFE Coating	Stainless Steel, PTFE Coating	Stainless Steel, PTFE Coating
ENERGY ABSORBER COVER	Polycarbonate with overmolded rubber	Polycarbonate with overmolded rubber	Polycarbonate with overmolded rubber
CARABINERS	Triple lock aluminum 30 kN minimum breaking strength	Triple lock aluminum 30 kN minimum breaking strength	Triple lock aluminum 30 kN minimum breaking strength
USERS	Max 2 users	Max 2 users	Max 2 users
SPAN TYPE	Single span only	Single span only	Single span only
PHYSICAL WEIGHT	17.4 lb. (7.9 kg)	17.4 lb. (7.9 kg)	24.3 lb. (11 kg)
RFID	Yes	Yes	Yes
COMPATIBILITY	MSA Cable Temporary Horizontal Lifeline System is designed for use with compatible MSA components, connectors, and subsystems.	MSA Cable Temporary Horizontal Lifeline System is designed for use with compatible MSA components, connectors, and subsystems.	MSA Cable Temporary Horizontal Lifeline System is designed for use with compatible MSA components, connectors, and subsystems.
STANDARDS	OSHA 29 CFR 1910.140 / 1926.502	OSHA 29 CFR 1910.140 / 1926.502	OSHA 29 CFR 1910.140 / 1926.502

**MSA Indonesia**  
Kompleks Multiguna Kemayoran No. 1-K  
Jl Rajawali Selatan Raya Blok C5 No.2  
Jakarta, 14410, Indonesia  
Email: msa.indonesia@MSAsafety.com

**MSA Safety Malaysia Sdn Bhd**  
No.22, Jalan PPU 2A,  
Taman Perindustrian Puchong Utama,  
47100 Puchong,  
Selangor, Malaysia  
Phone: +603-9767 8800  
Fax: +603-8051 8081  
Email: msa.malaysia@MSAsafety.com

**MSA S.E. Asia Pte Ltd**  
35 Marsiling Industrial Estate Road 3  
#04-01, Singapore 739257  
Phone: +65 6350 4500  
Fax: +65 6350 4505  
Email: msa.singapore@MSAsafety.com

**MSA S.E. Asia Pte Ltd  
(Representative Office)**  
Room 2036 SPACES Phahon 19 Building  
No.1687/1 Phahonyothin Road Lad Yao Sub-district  
Chatuchak District Bangkok 10900 Thailand  
Phone: +66 2038 8023  
Fax: +66 2617 8214  
Email: msa.thailand@MSAsafety.com

**MSA Australia**  
11 Columbia Way  
PO Box 7325  
Baulkham Hills  
NSW 2153, Australia  
Phone: 61 2 9688 0333  
Customer Service: 1300 728 672  
Fax: (02) 9896 1835  
Email: aus.customerservice@MSAsafety.com

Note: This Bulletin contains only a general description of the products shown. While product uses and performance capabilities are generally described, the products shall not, under any circumstances, be used by untrained or unqualified individuals. The products shall not be used until the product instructions/user manual, which contains detailed information concerning the proper use and care of the products, including any warnings or cautions, have been thoroughly read and understood. Specifications are subject to change without prior notice. MSA is a registered trademark of MSA Technology, LLC in the US, Europe, and other Countries. For all other trademarks visit <https://us.msasafety.com/Trademarks>.

MSA operates in over 40 countries worldwide. To find an MSA office near you, please visit [MSAsafety.com/offices](https://www.msasafety.com/offices).